

Worldwide Safe and Vault, Inc.

Proudly announces the arrival of the only UL-Rated TRTL-15x6 on the Market.



Worldwide Diamond Vault UL-Rated TRTL-15x6 High Security Safe

U.L. Listed TRTL15x6 High Security Burglary Rating - The Diamond Vault TRTL15x6 is certified burglary resistant having surpassed Underwriters Laboratories most direct torch and tool attack.

Body - The safe has a total body thickness of 3 1/4". High strength alloys and our proprietary barrier material combine to provide multi-layer protection designed to withstand the most sophisticated attack by tools, torch or explosives.

Door - The door has a thickness of 6 1/2". The same high strength alloys and proprietary barrier material used to protect the body are repeated in the door.

Locks - U.L. listed manipulation resistant high strength Group 1 combination lock with spy proof dial are used on all TRTL15x6 safes. A high security auxiliary key lock is optional on all models.

Boltwork - Massive 1 1/2" diameter chromed high tensile steel bolts are driven both horizontally and vertically through reinforced bolt chambers by the safe's three-way boltwork mechanism.

Glass Relockers - Tempered glass plates are used to protect vital mechanisms. If attacked, the glass will shatter and cause the relockers to activate thereby preventing the safe from being opened.

Adjustable Shelves - All models are supplied with fully adjustable and removable shelves.

MODEL	INSIDE H X W X D	OUTSIDE H X W X D	WEIGHT	CUBIC FEET	NO OF SHELVES
DV-6032	60 x 32 x 21	66 1/4 x 38 1/4 x 33	4300 LB.	23.3	4

Worldwide Safe & Vault, Inc.

3660 N.W. 115th Avenue, Miami, Florida 33178 USA

Nationwide Toll Free: 800-932-2278

Local: 305-477-9266 * Fax: 305-477-9744

www.worldwidesafe.com

info@worldwidesafe.com