

LP Series Gun Safes



NEW! LP6036WE-LTG-F-BK-A

This safe meets or exceeds the standards for California-approved Firearms Safety Devices and the requirements of California Penal Code Section 12088, Gun Safe Standards

Fire Protection

- The LP6036, LP6030, LP6032 and LP5924 offer fire protection of 1200°F for a period of 45 minutes. Designed to maintain an interior temperature of less than 350°F.
- Palusol™ door seal expands up to 8 times its original thickness when exposed to high temperatures sealing safe contents from harm.

Distinctive Style

- The quality-packed, affordably-priced LP series offer an unbeatable value, featuring a rich velour back-cover and fire walls with durable American Oak wood finish exterior.
- Black textured finish with bold zinc die-cast polished brass logos.
- Polished brass, spy-proof dial (mechanical combination only) and "L" handle.
- External hinges easily provide full access to your safe.

Theft Defiant

- High strength unitized 12-gauge solid steel body.
- Massive 1 3/4" recessed door constructed of a 1/4" solid steel plate and a fire insulating material.
- Equipped with a Group II, key-changeable combination lock with brass spy-proof dial and ring.
- On Electronic Models: Equipped with an ESL10XL UL Listed Type 1 Electronic Lock with polished brass keypad.
- 3-way boltwork with 5 active 1 1/4" diameter chrome-plated steel locking bolts and three 1 1/4" deadbolts.
- Each safe offers 4 pre-cut anchor holes and 1 pre-cut electrical access hole.



NEW! LP5924WE-LTG-F-BK-A
Also available with mechanical combination

Attractive and durable American Oak wood finish interior



LP Series Gun Safes

Model	Outside H x W x D	Thickness		Weight	Interior Capacity	Bolts
		Door	Body			
LP-6032W	59 ¼ X 30 X 21	1 ¾"	12 ga.	632 Lbs	10-10-20	5
LP-5924W	59 ¼ X 24 X 18	1 ¾"	12 ga.	478 Lbs	8-8-16	5



Worldwide Safe & Vault, Inc.

3660 N.W. 115th Avenue, Miami, Florida 33178 USA

Nationwide Toll Free: 800-932-2278

Local: 305-477-9266 * Fax: 305-477-9744

www.worldwidesafe.com

info@worldwidesafe.com

