

U.L. Listed 2 Hour Fire and Impact Safes

Fire strikes and American Home or Business Approximately every 50 Seconds. Storing your documents in a Worldwide Fire Safe is the best protection money can buy. Our New Premium Fire Safes carry the U.L. Class 350, 2 Hour fire and impact rating keeping valuables safe from temperatures up to 1850 degrees and disastrous falls from a three story burning building.

Features:

The best warranty in the business. Lifetime fire replacement and one year parts and labor.

- U.L. listed Class 350°F two hour fire and impact rating.
- Safes withstand fires of up to 1850°F for two hours and a 30' drop – equivalent to falling through a two story burning building.
- Increased barriers for burglary protection. Impressive 3-1/2" thick recessed door with 5/8" thick front for excellent pry resistance.
- Handle activated locking mechanism with 7/8" diameter solid steel chrome plated locking bolts offering smooth operation.
- Internal anchor bolt hole with hardware.
- U.L. listed Group II key changeable combination lock with relock. 1 million possible combinations.
- Auxiliary spring-loaded relock device activated by severe attack.
- Heavy duty steel hinges provide additional security and smooth operation.
- For your convenience, rubber feet are standard on models UL1511 – 1812XD.
- Heavy duty rolling casters on UL2018 and up.
- Attractively accented with a brass-plated dial, brown powder coated handle, decorative emblems and plush velour interior.
- Available in durable Sandstone or Granite textured finishes.



Optional Extras

- Optional key-locking drawer provides additional secured storage for small valuables. Measures 5-7/8"H x 10-1/4"W x 10-3/8"D.
- **A variety of electronic digital locks to suit your exact needs.**



OPTIONAL ELECTRONIC SAFE LOCKS



U.L. Fire Resistive Rating Classification

Underwriter's Laboratories' fire resistant container testing procedures on the Class 350°F 2 hour Fire Labels.

U.L. Label/Class 350°F-one hour and Class 350°F-two hour. The safe will maintain an interior temperature less than 350°F when exposed to fire for a period of one hour at 1700°F or for a period of two hours at 1850°F. Safe must successfully undergo all other requirements for the Fire Endurance Test, Explosion Hazard Test and the

MODEL	INSIDE H X W X D	OUTSIDE H X W X D	Door Opening H x W	Cubic Inch Capacity	Weight	Interior/ Shelves
UL-1511	15 X 11 ½ X 12	21 ½ X 17 X 18	15 x 11 ½	2,070	215 LB.	2
UL-1812	18 ½ X 12 ½ X 12	25 X 18 X 18	18 ½ x 12 ½	2,775	260 LB.	2
UL-1812XD	18 ½ X 12 ½ X 17	25 X 18 X 23	18 ½ x 12 ½	3,931	310 LB.	2
UL-2018	20 X 18 X 18	30 ¼ X 25 ½ X 25 ½	20 X 18	6,480	495 LB.	2
UL-2818	28 X 18 X 18	38 ¼ X 25 ½ X 25 ½	38 ¼ X 18	9,072	695 LB.	2
UL-3918	39 X 18 X 18	49 ¼ X 25 ½ X 25 ½	49 ¼ X 18	12,636	835 LB.	2

Add 2" to Outside Depth for Handle/Hinge Protrusion

Worldwide Safe & Vault, Inc.

3660 N.W. 115th Avenue, Miami, Florida 33178 USA

Nationwide Toll Free: 800-932-2278

Local: 305-477-9266 * Fax: 305-477-9744

www.worldwidesafe.com

info@worldwidesafe.com