

Commercial Security Safe

The Worldwide CSC-Series offers an affordable solution when you want to protect your documents from fire and valuables from burglary attacks. During Extreme Testing Procedures the CSC Series Safes passed a 2-Hour, 350 Degree factory fire test certification.

Door:

Overall thickness of 4-5/8" and is constructed with a 2" defense barrier of outer and inner steel plates creating a burglary resistant structure enclosing a unique proprietary, fire resistant material.

Body:

Total protective thickness of 2-7/8" enclosing a unique, high-density fire and burglary resistant composite material.

Durable powder coated adjustable shelves.

Removable casters provide easy delivery and installation.

Fire Endurance:

2 hour, 350°F factory fire rating. Tested at temperatures up to 1700°F.

Heat expandable intumescent door seal guards contents against severe fires.

Locking Mechanism:

Two to four 1½" diameter solid steel chrome-plated locking bolts.

Two to three 1½" diameter solid steel dead bolts lock deep into body preventing door removal during a forced entry.

U.L. Listed Group II combination lock with chrome-plated spy-proof dial. Optional electronic locks available.

Lock protected by a tempered glass relock device.

Heavy duty steel hinges provide easy, smooth door operation.

One internal counter-sunk anchor hole and mounting hardware are provided to securely anchor safe.

Attractively accented with a full width fascia panel and matching three point handle, Durable and attractive gray textured finish.



Model No.	Inside H x W x D	Outside H x W x D	Cubic Inch Capacity	Bolts	Interior Shelves	Wt. Lbs
CSC-1413	14 x 12.5 x 12.2	19.5 x 18 x 19.9	2,135	4	1	256
CSC-1913	19 x 12.5 x 12.2	24.5 x 18 x 19.9	2,898	4	2	318
CSC-3018	30 x 18 x 16.3	35.5 x 23.5 x 24	8,802	7	3	462
CSC-4520	45 x 20 x 21.2	50.5 x 25.5 x 28.9	19,080	7	4	768

***ADD 2" TO DEPTH FOR DIAL AND HANDLE PROJECTION**

Worldwide Safe & Vault, Inc.

3660 N.W. 115th Avenue, Miami, Florida 33178 USA

Nationwide Toll Free: 800-932-2278

Local: 305-477-9266 * Fax: 305-477-9744

www.worldwidesafe.com

info@worldwidesafe.com



Interior temperature less than 350°F for a period of 2 Hours at 1700°F